
SEALLESS STEEL STRAPPING TOOL CH 47

MANUAL.
ONE TOOL OPERATION.
TENSIONS, SEALS, CUTS.



CH 47

One tool - Manual tensioning, sealing and cutting for flat surfaces without metal seal.

OPERATION




Ergonomic design and balance means little effort is needed for tensioning and sealing the strap.

Both straps are inserted into the sealing area. Tension and sealing is achieved with lever action. Top strap is cut with the sealing action. The result is a triple notch seal (as shown below) that is more efficient than the traditional metal seal.

FEATURES

The open construction permits fast and simple access to the tool parts. Wearing parts can be replaced by the operator. Only a few manipulations are required to adapt another strap width or thickness. A single tool for all screws. High tension capacity – 650 kg

DATA



CH47

Weight	3.5kg
Joint type	3 punches in strap layers
Tension	650kg
Strap width	13,16,19mm
Thickness	0.38mm – 0.63mm



CYKLOP SECURA PTY. LTD.

A.B.N. 61 002 908 349

WEB: www.secura.com.au

EMAIL: sales@secura.com.au

HEAD OFFICE

210 RAILWAY TERRACE
GUILDFORD, N.S.W. 2161
PH: (02) 96370888
FAX: (02) 9897 1222

POSTAL ADDRESS

P.O. BOX 837
GUILDFORD, N.S.W. 2161

VICTORIAN BRANCH

1/10 FITZGERALD RD
LAVERTON NORTH, VIC 3026
PH: (03) 9369 0711, 9369 0733
FAX: (03) 9369 0766
